



MATERIAL:BRASS
 THICKNESS:0.2
 HARDNESS:SH
 PLATING:SELECTIVE GOLD FLASH
 INSULATION O.D.:1.57 MAX.
 WIRE RANGE:(AWG)#24~28
 VOLTAGE RATING:AC/250V,DC/350V
 CURRENT RATING:AC,DC,3A
 FIRST INSERTION FORCE:0.25KG MAX. PER CIRCUIT
 SIXTH WITHDRAWAL FORCE:0.06KG MIN. PER CIRCUIT
 SQUARE OR ROUND PIN SIZE:0.25*(0.63MM)
 TEMPERATURE RANGE : -25°C TO +85°C

T:0.2±0.03
 L:9.7±0.25
 W:1.3±0.1
 W1:1.95±0.1
 IS:2.2±0.3
 WS:1.9±0.3
 H:1.9±0.25
 H1:1.6±0.25
 H2:3.0±0.5
 t:0.9±0.25

PULLING DIRECTION:



RoHS Compliant			
APPD. 核准	 SCALE	TOLERANCE 容許公差	PART NAME 品名 2.54mm TERMINAL BRASS MATERIAL SELECTIVE GOLD PLATING AWG24~28 1R=10KPCS ROHS
DWG. 製圖		UNIT 單位	
DATE 制表日	PAGE 張數	M M	REV. 版次
2012/9/6	1 OF 1	A 4	PART NO. 2510G