

CHARACTERISTICS

	ITEM	SPECIFICATION
Electrical Characteristics	Temp Range	-10°C~70°C
	Rated Power	Curve B:0.125W Other curve B:0.053W
	Max Operation Voltage	Curve B:200V Other curve B:150V
	Resistance Range	1KΩ~2MΩ
	Allow Desistance Tolerance	±20%(1MΩ or more30%)
	Rotational Noise	≤47mV
	Terminal Resistance	R≥250KΩ 0.1%R max 250KΩ >R>10KΩ 20Ω max 10 KΩ ≥R 10Ω max
	Resistance Law	A、 B、 C
	Dielectric	AC500V,1minute
	Insulation Resistance	More than 100MΩ at DC500V
Mechanical Characteristics	Rotational Torque	2~20 mN.m (20~200gf.cm)
	Total Rotational Angle	300° ±5°
	Rotary life	10,000 cycles
	Shaft Stopper Strength	6Kgf.cm
	Push Pull Strength	60 N
	Click position	Center detent or 10,20,40 position clicks
Soldering	≤260°C,	

ROTARY POTENTIOMETERS WITH METAL SHAFT)

General

-This specification is applied to potentiometers used for electronic equipment.

-Operating temperature: -10°C~70°C

-10°C~70°C

Features

- Long life model,low cost
- Better feeling,center detent available
- Special tapers.

Applications

-Multimedia, computer speaker, stereos, amplifier etc

QUOTLINE DRAWING AND MOUNTING HOLE DETAIL

